

# XENON XP ACCESSORIES GUIDE



Honeywell

# TABLE OF CONTENTS

- 1 Wall Mounts, Stands, Holders, and Covers
- 1 Charge and Communication Bases, Chargers, and Batteries
- 2 Cables and Power Supplies

# WALL MOUNTS, STANDS, HOLDERS, AND COVERS



1950GSR-2-2-X  
1950GHD-2-2-X  
1950GSR-2USB-2-X  
1950GHD-2USB-2-X

### 1950G Ratchet Stand

Provides a fixed stand for a corded scanner that enables presentation scanning and two-handed scanning.



50129064-001

### Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



STND-08R00-000-6

### Rigid Presentation Stand – 3”

Stand: gray, 8 cm (3 in) height, rigid rod, large oval weighted base, cradle for Xenon™ 1900 and Xenon XP 1950 corded scanners.



STND-15R00-000-6

### Rigid Presentation Stand – 6”

Stand: gray, 15 cm (6 in) height, rigid rod, large oval weighted base, Xenon cradle.

STND-22F00-001-6

### Flexible Presentation Stand – 9”

Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon cup.



VISOR-190X-XT

### Extended Sun Visor

Extended sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



VISOR 190X

### Sun Visor

Sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



UCOVERXENON

### Retractable Lanyard Cover

Fabric cover for hanging the scanner from a retractable lanyard.



VMHOLDERE-21029

### Forklift Holder

Forklift/vehicle-mounted holder for holding a Xenon XP 1950 corded scanner between scans.

# CHARGE AND COMMUNICATION BASES, CHARGERS, AND BATTERIES



BAT-SCN01A

### Battery Pack

Battery: Lithium-ion battery for Xenon 1902 and Xenon XP 1952 cordless scanners.



BAT-SCN05

### Smart Battery Pack

Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.



SUPCAP-SCN05

### SuperCap Pack

Super Capacitor: Lithium-ion battery for Xenon XP 1952 cordless scanners.



MB4-BAT-SCN01NADO

### 4-Bay Battery Charger – Desk Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).



MB4-BAT-SCN01NAWO

### 4-Bay Battery Charger – Wall Mount

4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

CCB10-010BT-07N	CCB11-010BT-07N	CCB12-010BT-HC	CCB13-010BT-07N	CCB15-010BT-HC
<b>1952 Presentation CCB – Black (Battery)</b>	<b>1952 Presentation CCB – Lyric White (Battery)</b>	<b>1952 Presentation CCB – Healthcare (Battery)</b>	<b>1952 Desktop/Wall-Mount CCB – Black (Battery)</b>	<b>1952 Desktop/Wall-Mount CCB – Healthcare (Battery)</b>
Xenon XP 1952 Presentation CCB, black, 10 m (32.8 ft), Bluetooth®.	Xenon XP 1952 Presentation CCB, white, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Presentation CCB, healthcare white, healthcare software.	Xenon XP 1952 Horizontal CCB, black, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Horizontal CCB, healthcare white, healthcare software.

## CABLES AND POWER SUPPLIES

CBL-020-300-C00	CBL-120-300-C00	CBL-220-300-C00	CBL-420-300-C00	CBL-500-150-S00
<b>RS-232 Power Cable</b>	<b>RS-232 Power Cable</b>	<b>RS-232 Power Cable</b>	<b>RS-232 Power Cable</b>	<b>USB Power Cable</b>
Cable: RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8 ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle.	Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3 m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).	USB Type A HSM 5V 1.5 m (5 ft) straight cable.
CBL-500-300-S00	CBL-500-500-C00	CBL-503-300-C00	CBL-600-300-S00	CBL-600-400-C00
<b>USB Power Cable</b>	<b>USB Power Cable</b>	<b>USB Power Cable</b>	<b>IBM Power Cable</b>	<b>IBM Power Cable</b>
Cable: USB, black, Type A, 3 m (9.8 ft), straight, 5V host power.	Cable: USB, black, Type A, 5 m (16.4 ft), coiled, 5V host power.	Cable: USB, black, 12V locking, 3 m (9.8 ft), coiled, 5V host power.	Cable: IBM 46xx Port 9b, black, 3 m (9.8 ft), straight, 12V host power.	Cable: IBM 46xx Port 9b, 12V power, coiled, 4 m (13.1 ft).
CBL-720-300-C00	CBL-MAG-300-S00	46-00525	46-00526	46-00528
<b>Keyboard Wedge Power Cable</b>	<b>RS-232 Power Cable</b>	<b>Power Supply – NA Plug</b>	<b>Power Supply – EU Plug</b>	<b>Power Supply – AU Plug</b>
Cable: KBW, black, PS2, 3 m (9.8 ft), coiled, 5V external power with option for host power.	Cable: RS-232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.	Power Supply: NA plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: EU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: AU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.
46-00529				
<b>Power Supply – CN Plug</b>				
Power Supply: CN plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.				

### Honeywell Safety and Productivity Solutions

9680 Old Bales Road  
Fort Mill, SC 29707  
800-582-4263  
[www.honeywell.com](http://www.honeywell.com)